

CKL-1000・2

HIGH-SPEED LIQUID & PASTE PACKAGING MACHINE FOR WALL PAPER DESIGN FILM

エンドレス専用高速液体粘体自動充填包装機

CKL-1000-2 is the space saving, high productivity liquid & paste packaging machine. With the lower film setting position and the rolls in different levels enabling the use of long film, it is designed to contribute to the high performance. As the high-speed liquid packaging machine with two rows of rollers (equipped with the heat roll device in first and second rows), CKL-1000-2 is highly valued by our customers for its economic efficiency and the stability. In addition, with the fluid sealing, it can package the product without allowing the air to enter in the bag.

本機は、省スペース・高生産性を追求したエンドレス、固定ピッチの粘体物・液体物充填包装機です。フィルム原反の取り付け位置を低く設置したうえ、段差ロールが標準装備されておりますので、長尺フィルムを掛ける事ができ、高生産性に貢献できる様に設計されています。本機は、2段ロール方式(1・2段目に熱ロール装備)の高速液体充填包装機として、その経済性と安定性において広くお客様にご好評を得ています。さらに液かみシールにより袋内に空気を入れずに包装する事ができます。

SPECIFICATIONS / 本体標準仕様

Filling Material: Liquid & paste

Packaging Form: 3-side sealing, 4-side sealing (Single/Double)

Packaging Capacity: 20-300 bags/min.

Filling Volume: 3-50cc

*The range of the filling volume may vary by the "property of the filling material" and the "feeding device".

Bag Size: Width 25-100mm Length 40-120mm

Number of Rows of Roll: 2

Film Width: 50-200mm

Film Diameter: ϕ 400mm(Max.)

Film Feeding Speed: 20m/min.(Max.)

*Actual filling speed may vary by the product pitch, the film material and the property of the filling material.

Power Consumption: Main Motors 0.75kw(Total) Heater Single phase 200V, 1kw \times 4

Total Power 3.15kw

*Power consumption may vary by the selected optional equipments including the filling pump.

Dimensions of Machine: 1,060mm(W) \times 900mm(L) \times 2,170mm(H)

Weight of Machine: Approx. 400kg

充填物: 液体・粘体

包装形態: 3方シール4方シール(シングル/ダブル)

包装能力: 20~300袋/分

充填容量: 3~50cc

※充填容量の計量範囲は「充填物の物性」と「供給装置」により異なります。

製袋寸法: 幅25~100mm 長さ40~120mm

ロール段数: 2

フィルム幅: 50~200mm

フィルム最大巻径: ϕ 400mm以内

フィルム送り量: 20m/分(MAX)

※実際の充填速度は、製品ピッチ・フィルムの素材・充填物の物性等により異なります。

使用電力: 主モータ0.75kw(合計) ヒータ単相00V 1kw \times 4本

合計消費電力3.15kw

※充填ポンプその他オプションの選択により使用電力が異なります。

機械本体寸法: 幅1060mm \times 奥行900mm \times 高さ2170mm

機械重量: 約400kg

